800.272.4381 www.rollemusa.com

CHAMPION SEMI-SLITTER

OVERVIEW

Rollem's semi-slitting machines offer superior semi-slitting/kiss-cutting technology that delivers consistent production—sheet after sheet—resulting in greater customer satisfaction. Exceptional stability and control, extreme speeds, and a simple setup that requires no skilled labor translate to greater profitability for your enterprise. Semi-slit multiple sizes and thicknesses of paper with confidence and eliminate costly overruns.

The Champion SS is the top choice of sign and label producers everywhere to kisscut labels and PSA (pressure sensitive adhesive) stickers. Rollem separates itself from the competition with the largest range of semi-slitters on the market today, totaling five model sizes up to 42" in width.

Semi-slitting blade

PRODUCTS

- Labels
- Nameplates
- Industrial Components
- StickersI
- Retail Tags
- Promotional Graphics...and much more!

KEY BENEFITS

- Back or face-slit with precisely controlled cuts and easy depth adjustment on all types of liner stocks.
- Accuracy, consistency and easy operation result in greater customer satisfaction and higher profits
- Produce custom jobs and keep control and profits in-house
- Easy setup requiring no skilled labor
- Champion SS is available in a variety of configurations for your specific needs



- Back-slit liners of face-slit stocks with the highest dregree of accuracy
- Spring-loaded, pressure-sensitive semi-slitting heads automatically adjust to the cutting surface to eliminate high and low cutting points
- 4" hardened concentric rollers stabilizes and supports the width of any sheet to ensure precision
- Unique rotary slitting process assures accuracy on virtually any length of cut
- Kiss-cut material from fine paper stocks, including mylar, to heavy guage plastics with superior stability and control
- Each sheet is cut individually (as opposed to traditional guillotine cutters)
 eliminating offsetting, varying sizes, or excessive pressure
- Includes the ability to "cut-score" card stocks. The partial cut provides crisp, clean lines to ship products flat and fold upon receipt.



Shaft with two semi-slitting blades



Variable speed controller



CHAMPION SS

FUNCTIONS			
	Single-head semi-slitter Semi-slit (kiss-cut), face slit, cut score		
STANDARD	3 control heads, 1 semi-slitting head		
SPEEDS	Up to 26,000/hr		
MARGIN OF ACCURACY	Within 1/10,000th of an inch		
MEDIA SPECIFICATIONS			
MINIMUM SHEET SIZE	4x4"		
MAXIMUM SHEET SIZE	18" 24" 30" 36" 42" (model size indicates max sheet width)		
STOCK HANDLING	1 mil to 40 point		

PHYSICAL SPECIFICATIONS				
MODELS	FOOTPRINT (INCHES)	WEIGHT	POWER SUPPLY	
CHAMPION SS 18"	48L x 36W x 66H	132lbs	220 volts, 1-phase AC	
CHAMPION SS 24"	48L x 42W x 66H	335 lbs	220 volts, 1-phase AC	
CHAMPION SS 30"	63L x 48W x 66H	385 lbs	220 volts, 1-phase AC	
CHAMPION SS 36"	73L x 54W x 66H	430 lbs	220 volts, 1-phase AC	
CHAMPION SS 42"	93L x 60W x 66H	480 lbs	220 volts, 1-phase AC	



